



STOCK SERVICE

Lamé con gamma infinita di colori metallizzati e con ampia coloritura a stock service. Morbidissimo e ultrasottile ideato per capi elegantissimi e preziosi. Grazie alla possibilità di tintura di colori su richiesta clienti si presta anche ad essere abbinato a tutti i fili della collezione per impreziosire i capi grazie alla sua raffinata coloritura femminile argentata o dorata. Utilizzato anche in calzetteria per la sua estrema morbidezza a contatto con la pelle. Possibili colori su richiesta clienti dalle 2 basi oro e argento GLITTER Nm 70 e Nm 140 oppure GLOSSY Nm 24 e Nm 42.

Infinite range of metallic colors lamé with a wide availability of stock service colors: it's the new super-soft ultrafine yarn for elegant, luxurious garments. the possibility of dyeing the yarn in shades to customers' requests, this yarn can be combined with all the yarns in the collection to embellish the knits to its refined feminine tints of silver or gold. Also used in hosiery for its extreme softness on contact with the skin.

Possible colors on customers' request from the two gold and silver bases GLITTER Nm 70 and Nm 140 or GLOSSY Nm 24 and Nm 42.

GLOSSY	NM 24	92% NYLON 8% METALLIZZATA	OPTIMAL CUSTOM COLOURS DYE LOTS
TITOLO NOMINALE - NOMINAL COUNT		92% NYLON 8% METALLIZED FIBRE	KG: 10* - 20* - 40* - 60* - 120
GLOSSY	NM 42	85% NYLON 15% METALLIZZATA	* CON SUPPLEMENTO - * WITH SURCHARGE
TITOLO NOMINALE - NOMINAL COUNT		85% NYLON 15% METALLIZED FIBRE	COTTE SPECIALI - SPECIAL DYELOTS
CONFEZIONE OTTIMALE COLORI STOCK SERVICE: SCATOLA DA 10 KG. E MULTIPLI SENZA SUPPLEMENTI			KG: 200 SOLO PER IL COLORE NERO - ONLY FOR BLACK COLOR
OPTIMAL PACKAGE STOCK SERVICE COLORS: 10 KG. BOX AND MULTIPLE WITHOUT SURCHARGE			KG: 4* SOLO PER CAMPIONARIO - ONLY FOR SAMPLING

INDICAZIONI PER L'UTILIZZO:

MACCHINA RETTILINEA FINEZZA 14 - 18 AD UN CAPO

LA LAVORAZIONE SEAMLESS HA MAGGIORI CRITICITA' DA DOVER VALUTARE DOPO LE VOSTRE PROVE CON IL NOSTRO UFFICIO TECNICO.

TOGLIERE LA CALZA DI PROTEZIONE DALLA ROCCA DEL FILATO PER EVITARE CHE LE DIFFERENZE DI TENSIONE, DURANTE LA SMACCHINATURA, CAUSINO DIFETTI.

PER EVITARE LA CADUTA DI STAFFE DALLA ROCCA, COLLOCARE LA ROCCA STESSA IN UNA VASCHETTA CONTENENTE RISO CHE AMMORTIZZA PERFETTAMENTE LA TENSIONE.

LAVORARE A PIU' GUIDAFILI ALTERNANDO ROCCHIE INTERE E AMMEZZATE.

NON RIPARAFFINARE.

VAPORIZZARE ADEGUATAMENTE IL MANUFATTO PER EVIDENZIARE L'EFFETTO "COMFORT". VALUTARE ATTENTAMENTE L'IMPATTO DEI NODI SUL CAPO IN QUANTO LA COSTRUZIONE ARTIGIANALE DEL FILATO NE DETERMINA LA PRESENZA.

CARATTERISTICHE TECNICHE:

TARIFFA DOGANALE: 56050000

NM 24: PESO A MQ 136 GR. DEL TELO DI CAMPIONARIO, PUNTO RASATO TRATTATO FIN. 14.

NM 42: PESO A MQ 132 GR. DEL TELO DI CAMPIONARIO, PUNTO RASATO TRATTATO FIN. 18.

ICI PILLING BOX TEST: UNI EN ISO 12945-1 (14400 GIRI) VALORE PILLING: 4 / 5 RELATIVO AL TELO DI CAMPIONARIO, PUNTO RASATO TRATTATO.

TIPO DI NODI: MANUALI. NUMERO MEDIO DI NODI PER ROCCA: 1 / 2

PER TIPOLOGIA FILATI FANTASIA UNO SCARTO DEL 6 - 8% È DA RITENERSI NELLA NORMA.

ISTRUZIONI DI TRATTAMENTO INDUSTRIALE RIFERITE AL NOSTRO CAMPIONARIO:

PRESTIRARE ENERGICAMENTE IL MANUFATTO.

TRATTAMENTO: 1 MINUTO, RAPPORTO BAGNO 1/20 (MATERIALE/ACQUA) - TEMPERATURA: 20° C.

AMMORBIDENTE: CATIONICO, CIRCA 3% PESO MATERIALE - ASCIUGATURA: A FREDDO

I COLORI POSSONO PRESENTARE RETRAZIONI LEGGERMENTE DIVERSE TRA DI LORO E I VARI PUNTI MAGLIA CONDIZIONANO IL RIENTRO AL LAVAGGIO.

SI RACCOMANDA UN CONTROLLO PRELIMINARE ALLA PRODUZIONE INDUSTRIALE, IN MODO DA OTTIMIZZARE LE RESE PER LE QUALI NON SIAMO RESPONSABILI. E' RACCOMANDATO IL TRATTAMENTO IN ACQUA IN MODO DA GARANTIRE LA STABILITA' DIMENSIONALE DEI CAPI.

INDICATIONS FOR USE:

FLAT KNITTING MACHINE GAUGE 14 - 18 FOR 1 PLY

THE SEAMLESS KNITTING IS MORE CRITICAL, PLEASE EVALUATE YOUR TESTS WITH CARE AND THEN WITH OUR TECHNICAL DEPARTMENT.

IN ORDER TO PREVENT THE FORMATION OF KNITTING DEFECTS CAUSED BY DIFFERENCES IN YARN TENSION, TAKE OUT THE PROTECTION WRAPPING FROM THE CONE.

TO PREVENT THE YARN FROM FALLING UNDERNEATH THE CONE WHEN KNITTING, PLACE THE CONE IN A BOWL CONTAINING RICE, WHICH PERFECTLY REGULATES THE TENSION.

DO NOT USE A SINGLE FEED BUT AS MULTIFEED KNITTING ALTERNATIVE FULL AND HALF CONES. WE SUGGEST NOT RE-WAX.

STEAM ADEQUATELY IN ORDER TO FULLY DEVELOP THE "COMFORT" CHARACTERISTICS.

CAREFULLY CONSIDER THE IMPACT OF THE KNOTS ON THE GARMENT BECAUSE THE ARTISAN CONSTRUCTION OF THE YARN DETERMINES THEIR PRESENCE.

TECHNICAL NOTES:

CUSTOMS CODE: 56050000

NM 24: SQ. METER WEIGHT: 136 GR. REFERRING TO SAMPLE JERSEY STITCH WASHED GG. 14.

NM 42: SQ. METER WEIGHT: 132 GR. REFERRING TO SAMPLE JERSEY STITCH WASHED GG. 18.

ICI PILLING BOX TEST: UNI EN ISO 12945-1 (14400 TURNS) 4 / 5 PILLING VALUE, REFERRING TO SAMPLE JERSEY STITCH WASHED.

KIND OF KNOTS: MANUAL. AVERAGE NUMBER OF KNOTS PER CONE: 1 / 2

FOR FANCY YARNS A WASTE OF 6 - 8% CAN BE CONSIDERED NORMAL.

INDUSTRIAL FINISHING INSTRUCTIONS REFERRED TO OUR COLLECTION:

STRONG PRE-IRONING THE GARMENT.

TREATMENT: 1 MINUTE, BATH RATIO 1/20 (MATERIAL/WATER) - TEMPERATURE: 20° C.

SOFTENERS: CATIONIC, ABOUT 3% OF MATERIAL WEIGHT - DRY: COLD

THE COLORS MAY HAVE SLIGHTLY DIFFERENT RETRACTION AND THE VARIOUS STITCHES WILL INFLUENCE THE SHRINKAGE TO WASHING.

WE RECOMMEND TO CHECK IT BEFORE ENTERING BULK PRODUCTION, SO AS TO OPTIMIZE THE PERFORMANCES FOR WHICH WE DO NOT REMAIN RESPONSIBLE. WE RECOMMEND A TREATMENT IN WATER SO AS TO GUARANTEE THE DIMENSIONAL STABILITY OF GARMENTS.

SOLIDITA' : VALORI MEDI INDICATIVI - FASTNESS: INDICATIVE AVERAGE VALUES

LAVAGGIO IN ACQUA A 30°C. WATER WASHING AT 30°C. (UNI EN ISO 105 C06)	3	LAVAGGIO A SECCO DRY CLEANING (UNI EN ISO 105 X05)	4
LUCE LIGHT (UNI EN ISO 105 B02)	3 - 4	TINTO MATASSE HANK DYED	

PER COLORI CHIARI E BIANCO, LA SOLIDITA' ALLA LUCE E' INFERIORE DI CIRCA 1 PUNTO DAI

VALORI INDICATIVI DELLA SCHEDA CHE SI RIFERISCONO AI COLORI DELLA CARTELLA.

LE SOLIDITA' DEI COLORI A CAMPIONE VA DEFINITA CON I NOSTRI UFFICI COMMERCIALI.

FOR LIGHT AND WHITE COLORS THE FASTNESS TO LIGHT IS LOWER OF APPROX. 1 POINT FROM

THE INDICATIVE VALUES OF THE TECHNICAL SHEET WHICH REFER TO COLOR CARD COLORS.

THE FASTNESS OF SPECIAL COLORS MUST BE CONFIRMED WITH OUR SALES OFFICES.

ISTRUZIONI DI MANUTENZIONE:

CAPI IN TINTA UNITA: LAVARE DELICATAMENTE A SECCO OPPURE IN ACQUA A 30°C. CON SAPONE NEUTRO.

CAPI RIGATI O COLORI CONTRASTANTI: E' RACCOMANDATO IL LAVAGGIO A SECCO, ADEGUANDO I SIMBOLI DI MANUTENZIONE. RIVOLGERSI ALL'UFFICIO COMMERCIALE PER VALUTARE LA POSSIBILITA' DI TRATTAMENTI E COSTI, PER RAGGIUNGERE SOLIDITA' MAGGIORI.

ASCIUGARE IN PIANO SUBITO DOPO IL LAVAGGIO. NON ESPORRE CAPI UMIDI A LUCE DIRETTA.

I VARI PUNTI MAGLIA CONDIZIONANO IL RIENTRO AL LAVAGGIO ED E' SEMPRE NECESSARIO EFFETTUARE LE PROVE RELATIVE A QUANTO DICHIARATO NELLE ETICHETTE DI MANUTENZIONE.

SI CONSIGLIA DI EFFETTUARE SEMPRE UN CONTROLLO PRELIMINARE ALLA PRODUZIONE INDUSTRIALE AL FINE DI GARANTIRE LA CONFORMITA' DELLE TAGLIE.

CARE INSTRUCTIONS:

ONE COLOUR GARMENTS: DRY CLEAN DELICATELY OR WASH IN 30°C. WATER WITH NEUTRAL SOAP.

STRIPED OR MORE COLOUR GARMENTS: WE RECOMMEND DRY CLEAN ADAPTING THE CARE SYMBOLS. PLEASE CONTACT THE SALES OFFICE TO EVALUATE THE POSSIBILITY OF TREATMENTS AND COSTS TO ACHIEVE HIGHER FASTNESS.

DRY FLAT, IMMEDIATELY AFTER WASHING. DO NOT EXPOSE WET GARMENTS TO DIRECT LIGHT.

SHRINKING AFTER WASHING DEPENDS ON THE KIND OF STITCH USED, AND IT IS ALWAYS NECESSARY TO CARRY OUT TESTS RELATED TO WHAT IS STATED ON THE MAINTENANCE LABELS.

IT IS ADVISABLE TO ALWAYS CARRY OUT A PRE-PRODUCTION INSPECTION OF INDUSTRIAL PRODUCTION IN ORDER TO GUARANTEE SIZE CONFORMITY.

SIMBOLI DI MANUTENZIONE INTERNAZIONALI - UNI EN ISO 3758 : 2012 - INTERNATIONAL CARE SYMBOLS

CAPI IN TINTA UNITA



ONE COLOUR GARMENTS

CAPI RIGATI O COLORI CONTRASTANTI



STRIPED OR MORE COLOUR GARMENTS

filati BE.MI.VA.